




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04Q 7/38		A1	(11) International Publication Number: WO 00/59255
			(43) International Publication Date: 5 October 2000 (05.10.00)
(21) International Application Number: PCT/US00/08470		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 30 March 2000 (30.03.00)			
(30) Priority Data: 60/126,872 30 March 1999 (30.03.99) US 09/290,090 12 April 1999 (12.04.99) US			
(71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LTD. [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).			
(72) Inventor; and (75) Inventor/Applicant (for US only): MCCLURE, Kenneth [US/US]; 2616 Laramie Street, Irving, TX 75062 (US).		Published With international search report.	

(54) Title: SCANNING GUARD TIMER FOR MOBILE TELEPHONES



(57) Abstract

A method and system of background scanning of an evaluated system by a mobile station without missing paging frames on a registered system. The registered system is the system in which the mobile station has registered and will receive pages. The evaluated system is the system from which the mobile station must retrieve parameters. The various disclosed embodiments use the periodicity of the paging information to set a guard timer that will force the system back to the registered system before the paging information in the next time slot is missed. In an embodiment, after receiving a paging frame, the mobile station starts the guard timer (at 304) and begins evaluating another system by searching for system parameters. The delay time (A) is the time between receiving a paging frame and starting the guard timer. If the mobile station receives system parameters prior to the guard timer timing out (at 306), the guard timer is halted (at 310) and the mobile station is switched back to the registered system. If no system parameters are received, the guard timer will timeout (at 306) and the mobile station will switch back to the registered system with enough delay time (B and C) to receive the next paging frame.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SCANNING GUARD TIMER FOR MOBILE TELEPHONES

Field of the Invention

This invention relates to background scanning for a more preferred system in mobile communications systems, and particularly to elimination of missed pages during such background scanning.

Background of the Invention

In a TDMA cellular radiotelephone system, each radio channel is divided into a series of time slots, each of which contains a burst of information from a data source, e.g., a digitally encoded portion of a voice conversation. The time slots are grouped into successive TDMA frames having a predetermined duration. The number of time slots in each TDMA frame is related to the number of different users that can simultaneously share the radio channel. If each slot in a TDMA frame is assigned to a different user, the duration of a TDMA frame is the minimum amount of time between successive time slots assigned to the same user. The successive time slots assigned to the same user, which are usually not consecutive time slots on the radio carrier, constitute the user's digital traffic channel (or DTC), which may be considered a logical channel assigned to the user. As described in more detail below, digital control channels (DCCs) can also be provided for communicating control signals, and such a DCC is a logical channel formed by a succession of usually non-consecutive time slots on the radio carrier.

In North America, these features are currently provided by a digital cellular radio telephone system called the digital advanced mobile phone service (D-AMPS), some of the characteristics of which are specified in the interim standard IS-54B, "Dual-Mode Mobile Station-Base Station Compatibility Standard", published by the Electronic Industries Association and Telecommunications Industry Association (EIA/TIA). Interim Standard (IS) 136 (promulgated by the Telecommunications Industry Association) adds a Digital Control Channel (DCCH) to IS-54B. References to IS-54B in this document are meant to incorporate IS-136.

According to IS-54B, each TDMA frame consists of six consecutive time slots and has a duration of 40 milliseconds (ms). Thus, each radio channel can carry from three to six DTCs (e.g., three to six telephone conversations) depending on the source rates of the speech coder/decoders (codecs) used to digitally encode the

conversations. Such speech codecs can operate at either full-rate or half-rate, with full-rate codecs being expected to be used until half-rate codecs that produce acceptable speech quality are developed. The TDMA cellular system operates in a buffer-and-burst, or discontinuous-transmission, mode: each mobile station transmits (and receives) only during its assigned time slots. At full rate, for example, a mobile station might transmit during slot 1, receive during slot 2, idle during slot 3, transmit during slot 4, receive during slot 5, and idle during slot 6, and then repeat the cycle during succeeding TDMA frames. Therefore, the mobile station, which may be battery-powered, can be switched off, or sleep, to save power during the time slots when it is neither transmitting nor receiving. In the IS-54B system in which the mobile does not transmit and receive simultaneously, a mobile can sleep for periods of at most about 27 ms (four slots) for a half-rate DTC and about 7 ms (one slot) for a full-rate DTC.

Note that the term mobile station is used herein to refer to a radio unit in a communications system, which includes radio units that are "stationary" or "fixed", and is not limited to being "mobile." The term "mobile" unit is used herein merely because of its wide acceptance and clear meaning in the communications arts.

In addition to voice or traffic channels, cellular radiocommunication systems also provide paging access, or control, channels for carrying call-setup messages between base stations and mobile stations

In general, the transmission rate of the DCC need not coincide with the half-rate and full-rate specified in IS-54B, and the length of the DCC slots may not be uniform and may not coincide with the length of the DTC slots. The DCC may be defined on an IS-54B radio channel and may consist, for example, of every n -th slot in the stream of consecutive TDMA slots. In this case, the length of each DCC slot may or may not be equal to 6.67 ms, which is the length of a DTC slot according to IS-54B. Alternatively (and without limitation on other possible alternatives), these DCC slots may be defined in other ways known to one skilled in the art.

Figure 1 shows a general example of a forward DCC configured as a succession of time slots 1, 2, . . . , N , . . . belonging to a particular DCC. These DCC slots may be defined on a radio channel such as that specified by IS-54B, and may consist, for example, of every n -th slot in a series of N consecutive slots. The DCC slots shown in Figure 1 are organized into superframes (SF)', and each superframe includes a number of logical channels that carry different kinds of information. One or more DCC slots may be allocated to each logical channel in the superframe.

Of the slots in a Superframe available for signaling, some are designated by the base station (BMS) for broadcast (point-to-multipoint) messaging and the rest for point-to-point messaging. In order for the base station to be able to notify (or "page") a mobile station (MS) of an incoming call (or other impending transaction), the mobile station is assigned to one and only one of the slots in a Superframe available for point-to-point messaging on the forward DCC (i.e., that portion of the DCC used to transmit messages from the base station to the mobile station).

As used herein, the terms "page" and "page message" refer to one or more slots of data transmitted from a base station over the point-to-point messaging channel that contains information intended to signal one (or possibly more) of a plurality of mobile stations that such mobile stations have an incoming call. (An incoming call can be, for example, a voice call or any other type of incoming call capable of being serviced by the base station and mobile stations.) The term "non-page message" refers to any slots of data transmitted over the point-to-point messaging channel that are not "page messages".

Figure 1 also shows an exemplary downlink superframe, which includes at least three logical channels: a broadcast control channel (BCCH) including six successive slots for overhead messages; a paging channel (PCH) including one slot for paging messages; and an access response channel (ARCH) including one slot for channel assignment and other messages. The remaining time slots in the exemplary superframe of Figure 1 may be dedicated to other logical channels, such as additional paging channels or other channels. Since the number of mobile stations is usually much greater than the number of slots in the superframe, each paging slot is used for paging several mobile stations that share some unique characteristic, for example, the last digit of the MIN.

Although IS-54B provides for digital traffic channels, more flexibility is desirable in using digital control channels having expanded functionality to optimize system capacity and to support hierarchical cell structures, i.e., structures of macrocells, microcells, picocells, etc. The term "macrocell" generally refers to a cell having a size comparable to the sizes of cells in a conventional cellular telephone system (e.g., a radius of at least about 1 kilometer), and the terms "microcell" and "picocell" generally refer to progressively smaller cells. For example, a microcell might cover a public indoor or outdoor area, such as a convention center or a busy street, and a picocell might cover an office corridor or a floor of a high-rise building.

From a radio coverage perspective, macrocells, microcells, and picocells may be distinct from one another or may overlap one another to handle different traffic

patterns or radio environments. Each of these types of cells has a base station which transmits at least one control channel. Thus, a number of neighboring control channels are present for a mobile or remote unit to evaluate as a possible replacement for the current serving control channel to which it is locked.

Accordingly, DCCs will be periodically evaluated by the mobile station for possible control channel reselection. For example, when in an idle state i.e., switched on but not making or receiving a call, a mobile station in an IS-54B system tunes to and then regularly monitors the strongest control channel (generally, the control channel of the cell in which the mobile station is located at that moment) and may receive or initiate a call through the corresponding base station. Re-tuning is required when the mobile station receives signals from the serving base station (registered station) at such a degraded level that the mobile station is forced to tune to a control channel of a nearby alternative base station.

The initial tuning and subsequent re-tuning to control channels are both accomplished automatically by scanning all the available control channels at their known frequencies to find the best control channel. The terms scan or scanning as used in this document, can refer to, for example, signal strength measurement, actual signal decoding, or any other method of evaluating a signal.

When a control channel with good reception quality is found, the mobile station remains tuned to this channel until the quality deteriorates again. In this way, mobile stations are relatively continuously in communication with the cellular system.

According to a more recent innovation in cell reselection disclosed in U.S. Pat. No. 5,353,332 to Raith and Muller, each control channel in each cell is configured to broadcast information, including system parameters, about the presence, if any, of other cells and the characteristics of those cells including minimum quality criteria, power requirements, etc. Typically, information about the presence of other cells is broadcast about neighboring cells. For instance, a neighboring cell may be adjacent to, overlapping, or non-contiguous from the broadcasting cell.

A mobile periodically scans, during idle mode, the neighboring control channels in the coverage area that the mobile is located in to determine in which cell it should be locked (or registered). This process is known as background scanning. Each control channel includes a neighbor list. The neighbor list identifies other control channels which mobiles locked to that control channel should periodically evaluate. Thus, a mobile may continuously select cells to be locked to based on the existing location of the mobile and quality criteria, such as received signal strength,

associated with the cells. The cell to which the mobile may be locked is the cell in which the mobile satisfies the quality criteria associated with the cell.

While in the idle state, and in addition to evaluating control channels as potential reselection candidates, a mobile station must monitor the control channel for paging messages addressed to it. When the base station needs to "page" the mobile station, that is, notify the mobile station that it has an incoming call (or other impending transaction), the base station transmits a "page message" or a "hard page" in the assigned slot for the mobile station. Under quiescent conditions, the mobile station need only monitor this assigned slot in the Superframe. Thus, the mobile station is able to "sleep" while the other 31 slots of the Superframe are being transmitted. In addition, because every other Superframe transmitted (i.e., every primary Superframe) by the base station is followed by a Superframe (secondary Superframe) having identical point-to-point paging slots, the mobile unit can sleep during every other entire Superframe. For other types of point-to-point traffic, however, the mobile station is not assigned to a specific slot in a Superframe; rather, when it is expecting a "non-page message," i.e., not a message intended to notify the mobile station of an incoming call (or other impending transaction), from the base station, the mobile station is required to search for non-page messages addressed to itself in each slot available for point-to-point messaging within the Superframe.

Currently, mobile stations are hashed to a slot in the Superframe (called a PCH Subchannel) where the mobile station expects to receive page traffic. Nominally, the mobile station is required to read this same slot in every other Superframe.

Figure 2 depicts a block diagram of the various elements in a time division multiple access digital control channel. A TDMA Frame 200 is depicted which is made up of six slots 202, 204, 206, 208, 210, 212. Each slot 202, 204, 206, 208, 210, 212 is transmitted through the communications channel, consisting primarily of air, during a 6.67 ms period of time, such that the TDMA Frame 200 is 40 ms in duration. In accordance with current TDMA conventions, a TDMA channel is made up of every third slot within the TDMA Frame. Thus, slots 1 and 4 (202, 208) are a part of one TDMA channel, slots 2 and 5 (204, 210) part of another TDMA channel, and slots 3 and 6 (206, 212) yet another.

Within each TDMA channel, groups of 32 TDMA blocks (and thus 32 slots) comprise a Superframe 214, having a duration of 640 ms. A total of three Superframes, one per TDMA channel, is transmitted every 640 ms. Within each Superframe 214, a portion of the slots is designated as the Broadcast Channel

(BCCH), another portion Reserved, and another portion the point-to-point messaging channel. Each mobile unit monitoring a particular base station is assigned to monitor a particular PCH subchannel, i.e., a particular slot within the point-to-point messaging channel.

As an example, slot 24 (216) may be the monitored PCH subchannel for a particular group of mobile units within a cell (assuming for a given case slot 24 is part of the point-to-point messaging channel). The PCH subchannel may contain any of a plurality of point-to-point communications encoded in 324 bits, which make up the PCH subchannel.

The mobile unit, is not always monitoring the digital control channel (DCCH) for Page Messages. Each slot in a given digital control channel has a specified function (in accordance with IS-136). Some, called broadcast control channel (BCCH) slots, are allocated to carry overhead information to all mobile stations that may be monitoring a particular digital control channel (point-to-many). Others, called Short Message Service, Paging, and Access Response Channel (SPACH) slots, are used by the base station to carry point-to-point Messages to a specific mobile station. Together the BCCH and the SPACH (as possibly some Reserved slots) comprise a Superframe. Each Superframe is made up of a total of thirty-two slots (in a full-rate DCCH), each allocated as a BCCH slot or a SPACH slot (or possibly a Reserved slot). Superframes are transmitted in pairs referred to as Primary and Secondary Superframes, respectively. In a quiescent system, the mobile station is only required to monitor a single SPACH slot (called its Paging Channel (PCH) Subchannel) in every other Superframe, i.e., in every Primary Superframe.

In digital cellular systems, there are several standards requiring the mobile station to search for a system while registered on another (background scanning). This search takes place on the mobile station without any assistance from the base station (as in reselection or handoff). Furthermore, this search takes place without any coordination between the mobile station and the base station.

There are currently several specifications requiring this type of background scanning. For example, Intelligent Roaming for ANSI 136 utilizes a database to determine the priority of a system. While registered on certain low priority systems, the mobile station must search for a system of higher priority.

Another example of a specification requiring background scanning is the Inter-Network Roaming Selection specification from GSM North America (GSM NA). This specification requires a priority database to determine the best system in AMPS and GSM 1900. While registered to a low priority system, the mobile station must

search another protocol for a higher priority system. The ANSI-136 Intelligent Roaming and Inter-Network Roaming Selection specifications are the first of many specifications dealing with prioritized system selection requiring background scanning.

The drawback of background scanning, however, is that, during the period of time the mobile station is retrieving identification parameters from the base system under investigation (or evaluation) as a possibly better system, the mobile station can miss pages on the system to which it is registered. This aspect of the background scanning is addressed in the Intelligent Roaming specification by forcing the base station to repeat a missed page after five seconds. This gives a mobile station in the TDMA/AMPS environment a second chance to receive the page.

The GSM NA specification does not address this possibility of missed pages. Therefore, a mobile station conforming to the GS NA standard can fatally miss a page if the unrepeated page goes undetected by the mobile station.

Summary of the Invention

The present invention discloses a method and system of background scanning of a base system under evaluation by a mobile station without missing pages on the registered system. The registered system is defined as the system in which the mobile station has registered and will receive pages. The system under evaluation is the system from which the mobile station must retrieve system parameters (the possibly higher priority system). The various disclosed embodiments use the periodicity of the paging information to set a guard timer that will force the mobile station back to the registered system before the paging information in the next time slot is missed. After receiving the paging information, the mobile station can continue its search and evaluation of base systems. In other words, the guard timer breaks the background scan into smaller segments that are performed between retrievals of paging information.

One or more of the disclosed embodiments provides at least the following advantages:

- Ability to operate in a dual-mode (or greater) environment without regard to particular paging protocols.

- Reduction in missed pages occurring during base system evaluation;

- Reduced traffic on paging channels by eliminating the need to force a base station to repeat a page after 5 seconds of no response; and

- Faster mobile station responses to base system paging. In an embodiment of the invention, a mobile station receives its paging frame from the base station on

which it is currently registered. Receipt of the paging frame triggers a scanning guard timer timing sequence. During the timing sequence, the mobile station scans and evaluates an other base station. At the end of the timing sequence, the scanning guard timer forces the mobile station to stop scanning and switch back to the registered station to receive the next paging frame from the registered base station.

Brief Description of the Drawings

The disclosed inventions will be described with reference to the accompanying drawings, which show important sample embodiments of the invention and which are incorporated in the specification hereof by reference, wherein:

Figure 1 shows a general example of a forward DCC configured as a succession of time slots 1, 2, . . . , N, . . . belonging to a particular DCC.

Figure 2 depicts a block diagram of the various elements in a time division multiple access digital control channel.

Figure 3 depicts expiration of the guard timer prior to receiving system parameters.

Figure 4 depicts a block diagram of a cellular communications system suitable for implementing the disclosed embodiments.

Figure 5 depicts the guard timer being halted after receiving system parameters.

Figure 6 depicts a block diagram of a mobile station that can make use of the disclosed embodiments.

Detailed Description of the Preferred Embodiments

The numerous innovative teachings of the present application will be described with particular reference to the presently preferred embodiment. However, it should be understood that this class of embodiments provides only a few examples of the many advantageous uses of the innovative teachings herein.

The guard timer provides a method to return to a mobile station to a registered system from a background scan (on a system under evaluation) so that no paging frame is missed. The guard timer is a control program loaded and executed by the mobile station immediately after the it receives the paging frame (slot, or equivalent) that is responsible for containing any paging information for the mobile station. The guard timer is set to expire after a controlled time period allowing the mobile to receive the next paging frame (or equivalent) that is responsible for containing any paging information for the mobile station.

Figure 3 depicts expiration of the guard timer prior to receiving system parameters. After receiving a paging frame, the mobile station starts the guard timer at time hash 304. A system specific delay (represented by *A*) denotes the delay time, if any, in the mobile station that occurs between receiving of the paging frame and starting the guard timer. Such system specific delays can include, for example, software and hardware execution delays, task switching, and other system functions that delay the mobile station in switching its receiver to process the alternative frequency of the evaluated system. Such delays are system (hardware and software) dependent, differing depending on mobile station architecture. Other delays can include, for example, delays due to the physical movement of the mobile station in between paging frames or other ambiguities in the distance of the mobile station from the base station due to the movement of the mobile station. In the example depicted in Figure 3, system parameters for the evaluated system are being transmitted in frame 302. Before any system parameters are received from the base system being evaluated, the guard timer expires at time hash 306. The mobile station, then begins to switch from monitoring the evaluated system to monitoring the registered system. A second system specific delay (represented by *B*) denotes the delay time, if any, in the mobile station that occurs between the expiration of the guard timer 306 and the switch of the mobile receiver from the evaluated system back to the registered system, at time hash 308. Again, such system specific delays can include, for example, software and hardware execution delays, task switching, and other system functions that delay the mobile station in switching its receiver to process the alternative frequency of the evaluated system. Such delays are system (hardware and software) dependent, differing depending on mobile station architecture. The system specific delay (represented by *C*) denotes the delay time, if any, required by the mobile station in switching back to the registered system and the time when the mobile station is capable of successfully processing a paging frame (synchronization time). Such system specific delays can include, for example, software and hardware execution delays, task switching, and other system functions that delay the mobile station in switching its receiver to process the alternative frequency of the evaluated system. Such delays are system (hardware and software) dependent, differing depending on mobile station architecture. Since the parameters 302 were not received, the mobile station will repeat this process again after processing the paging frame.

In the presently preferred embodiment, the period for the guard timer must take into account the delays mentioned above (*A*, *B*, and *C*). The guard timer should

be set no greater than the sum of these delays subtracted from the period of time between paging frames or between same numbered frames in a superframe.

Figure 5 depicts the guard timer being halted after receiving system parameters. In Figure 5, after receiving the paging frame, the mobile station starts the guard timer. The mobile station receives the system parameters 302 from the evaluated system before the expiration of the guard timer. The guard timer is halted, at time hash 310, and the mobile station switches back to the registered system (after *C* delays) with ample time to receive the next paging frame.

Figure 4 depicts a block diagram of a cellular communications system suitable for implementing the disclosed embodiments. A cellular telephone system 10 has a plurality of mobile switching centers (MSC) 12, 14, 16, or mobile telephone switching offices (MTSO), that are connected to each other and to a public switched telephone network (PSTN) 18. Each of the mobile switching centers is connected to a respective group of base station controllers (BSC) 20, 22, 24. Each base station controller is connected to a group of individual base transceiver stations (BTS) 26, 28, 30. Each base transceiver station of the groups 26, 28, 30 defines an individual cell of the cellular telephone system.

Each base transceiver station of the groups 26, 28, 30 includes hardware and software functions required to communicate over communications channels of the system 10; and includes transmitters and receivers for communication with mobile telephone units. Each base transceiver station 26, 28, 30 also includes a plurality of individual standard receivers (StdR) 31 and scanning receivers (SR) 32 for scanning selected portions of the communications channel. Each base transceiver station 26, 28, 30 further includes digital multiplex equipment for transmission of audio traffic to its associated base station controller. It is the base transceiver stations 26, 28, 30, along with their associated base station controllers 20, 22, 24 and mobile switching centers, that perform the steps described herein in order to carry out one embodiment of the invention.

A plurality of digital mobile stations 33 is used with the system 10 for communication over the communications channel (or radio frequency traffic channel) with a particular base transceiver station of a particular cell in which the particular base transceiver station is located. According to the various disclosed embodiments, associated with each digital mobile station 33 is a scanning receiver 35 for scanning selected portions of the communications channel between the mobile unit 33 and the base transceiver station of serving and neighboring cells.

Each base station controller of the groups 20, 22, 24 implements audio compression/decompression, handles call establishment, disconnect, and handoff procedures, and allocates system resources between the individual base transceiver stations 26, 28, 30 associated with each of the base station controllers 20, 22, 24. More specifically, each base station controller performs handoff execution for transferring on-going communications from one cell to another within the group of base transceiver stations connected to the particular base station controller. Each base station controller communicates with its associated mobile switching center for effecting a handoff involving a cell or base transceiver station associated with a different base station controller. Each mobile switching center 12, 14, 16 processes all requests for calls, switching functions, as well as the mobility functions of registration, authentication and handoff.

Figure 6 depicts a block diagram of a mobile station 600 that can make use of the disclosed embodiments (like 33 and 35 described in Figure 4). The mobile station 600 includes, in this example:

A control head 602 containing an audio interface, i.e. a speaker 604 and microphone 606. The control head 602 generally includes a display assembly 608 allowing a user to see dialed digits, stored information, messages, calling status information, including signal strength, etc. The control head generally includes a keypad 610, or other user control device, allowing a user to dial numbers, answer incoming calls, enter stored information, and perform other mobile station functions. The control head also has a controller unit 634 that interfaces with a logic control assembly 618 responsible, from the control unit perspective, for receiving commands from the keypad 610 or other control devices, and providing status information, alerts, and other information to the display assembly 608;

A transceiver unit 612 containing a transmitter unit 614, receiver unit 616, and the logic control assembly 618. The transmitter 614 converts low-level audio signals from the microphone 606 to digital coding using a codec (a data coder/decoder) 620. The digitally encoded audio is represented by modulated shifts, for example, in the frequency domain, using a shift key modulator/demodulator 622. Other codes transmission utilized by the logic control assembly 618, such as station parameters and control information, may also be encoded for transmission. The modulated signal is then amplified 624 and transmitted via an antenna assembly 626;

The antenna assembly 626 contains a TR (transmitter/receiver) switch 636. The TR switch 636 is used to prevent simultaneous reception and transmission of a signal by the mobile station 600. The antenna assembly also contains at least one

antenna 638. Optionally, a different antenna may be coupled 640 to the antenna assembly.

A receiver unit which receives a transmitted signal via the antenna assembly 626. The signal is amplified 624 and demodulated 622. If the signal is an audio signal, it is decoded using the codec 620. The audio signal is then reproduced by the speaker 604. Other signals are handled by the logic control assembly 618 after demodulation 622; and

A logic control assembly 618 usually containing an application specific integrated circuit (or ASIC) combining many functions, such as a general purpose microprocessor, digital signal processor, and other functions, into one integrated circuit. The logic control assembly 618 coordinates the overall operation of the transmitter and receiver using control messages. The various disclosed embodiments make use of the logic control assembly to control scanning and evaluation of other base stations. Generally, the logic control assembly operates from a program that is stored in flash memory 628 of the mobile station. Flash memory 628 allows upgrading of operating software, software correction or addition of new features. Flash memory 628 is also used to hold user information such as speed dialing names and stored numbers. The various disclosed embodiments typically function from this or another section of the mobile station's memory.

In addition to flash memory 628, the mobile station will typically contain read only memory (ROM) 630 for storing information that should not change, such as startup procedures, and random access memory (RAM) 632 to hold temporary information such as channel number and system identifier.

In general, statements made in the specification of the present application do not necessarily delimit any of the various claimed inventions. Moreover, some statements may apply to some inventive features but not to others. As will be recognized by those skilled in the art, the innovative concepts described in the present application can be modified and varied over a tremendous range of applications, and accordingly the scope of patented subject matter is not limited by any of the specific exemplary teachings given.

For example, other wireless telecommunications standards, currently in existence or which may be created, may require different responses and evaluations of neighboring base systems. In turn, the guard timer or evaluation duration may need to be lengthened or shortened. Further, differing frame patterns or timing alterations may require changes in the guard timer.

As processor times increase and system specific delays decrease, it may become possible to evaluate more than one other base station between the paging frames of a registered base station. In such a case, modifications to the guard timer incorporating re-tuning to several frequencies and other delays may have to be incorporated.

As described above, mobile station architecture can affect the *A*, *B*, and *C* delay times. It is possible that some architectures may reduce one or more of these times to effectively zero.

Some standards in wireless communication can lengthen the page message times to be longer than one frame. For example, point-to-point message continuation is the process by which the base station sends a message over multiple point-to-point messaging slots. A mobile station responds to point-to-point messaging channel message continuation whenever it determines that a message addressed to its mobile station identification (MSID) number, sent by the base station, occupies more than one point-to-point messaging slot. A page message spanning more than 1 point-to-point messaging slot, when sent on a full-rate digital control channel, is transmitted using every other point-to-point messaging slot. A page message spanning more than 1 point-to-point messaging slot, when sent on a half-rate digital control channel, is transmitted using consecutive point-to-point messaging slots. If a page requiring more than one paging frame or slot is to be received, guard timing will need to be adjusted.

Additional general background, which helps to show the knowledge of those skilled in the art regarding the system context, and of variations and options for implementations, may be found in the following: TIA interim standards IS-136 and IS-54B; and Brodsky, *Wireless: The Revolution in Personal Telecommunications* (1995); all of which are hereby incorporated by reference.

Claims

What is claimed is:

- 1 1. A method of evaluating a base station without missing a paging frame, comprising
2 the steps of:
 - 3 receiving a first paging frame from a first base station;
 - 4 initiating a timing sequence after receiving said first paging frame;
 - 5 scanning for system parameters from a second base station; and
 - 6 receiving a second paging frame from said first base station.
- 1 2. The method of Claim 1, further comprising the step of halting said scanning step
2 when said system parameters from said second base station are received.
- 1 3. The method of Claim 1, further comprising the step of halting said scanning step
2 once said timing sequence is complete.
- 1 4. The method of Claim 1, wherein said second paging frame is the paging frame for
2 said mobile station which immediately follows said first paging frame.
- 1 5. The method of Claim 1, wherein the duration of said scanning step is limited to a
2 predetermined amount of time, said amount of time being dependent on the
3 amount of time between said first and second paging frames.
- 1 6. The method of Claim 1, wherein the duration of said scanning step is limited to a
2 predetermined amount of time said predetermined amount of time being
3 dependent on mobile station architecture.
- 1 7. The method of Claim 1, wherein the duration of said scanning step is limited to a
2 predetermined amount of time, said amount of time being dependent on the
3 amount of time required for said mobile phone to switch from said first receiving
4 step to said scanning step and from said scanning step to said second receiving
5 step.
- 1 8. The method of Claim 1, wherein said steps are performed by a mobile station .

1 9. A method of evaluating a base station without missing a paging frame,
2 comprising the steps of:
3 initiating a timing sequence after receiving a first paging frame from a first
4 base station;
5 selecting a second base station to be evaluated during said timing sequence;
6 scanning said second base station transmissions for system parameters; and
7 receiving a second paging frame from said first base station.

1 10. The method of Claim 9, further comprising the step of halting said scanning step
2 when said system parameters from said second base station are received.

1 11. The method of Claim 9, further comprising the step of halting said scanning step
2 once said timing sequence is complete.

1 12. The method of Claim 9, wherein said second paging frame is the paging frame for
2 said mobile station which immediately follows said first paging frame.

1 13. The method of Claim 9, wherein the duration of said scanning step is limited to a
2 predetermined amount of time said predetermined amount of time being
3 dependent on mobile station architecture.

1 14. The method of Claim 9, wherein the duration of said scanning step is limited to a
2 predetermined amount of time, said amount of time being dependent on the
3 amount of time between said first and second paging frames.

1 15. The method of Claim 9, wherein the duration of said scanning step is limited to a
2 predetermined amount of time, said amount of time being dependent on the
3 amount of time required for said mobile phone to switch from said first receiving
4 step to said scanning step and from said scanning step to said second receiving
5 step.

1 16. The method of Claim 9, wherein said steps are performed by a mobile station.

1 17. A system of wireless base station and mobile station communication, comprising:
2 first and second base stations transmitting paging frames and system
3 parameters; and
4 a mobile station registered with and receiving paging frames from said first
5 base station;
6 wherein said mobile station evaluates said second base station based on
7 transmitted system parameters of said second base station without missing
8 said paging frames from said first base station.

1 18. The system of Claim 17, wherein said mobile station can receive said system
2 parameters of said second base station only when said first base station is not
3 transmitting said paging frames.

1 19. The system of Claim 17, wherein receipt of a first paging frame triggers
2 evaluation of said second base station.

1 20. The system of Claim 17, wherein said mobile station stops receiving said
2 transmissions of said second base station once said system parameters from
3 said second base station are received.

1 21. The system of Claim 17, wherein said mobile station can receive said
2 transmissions of said second base station only during a predetermined amount of
3 time, said predetermined amount of time being dependent on the architecture of
4 said mobile station.

1 22. The system of Claim 17, wherein said mobile station can receive said
2 transmissions of said second base station only during a predetermined amount of
3 time, said predetermined amount of time being dependent on the amount of time
4 between said paging frames for said mobile station transmitted by said first base
5 station.

1 23. The system of Claim 17, wherein said mobile station can receive said
2 transmissions of said second base station only during a predetermined amount of
3 time, said amount of time being dependent on the amount of time required for
4 said mobile phone to switch from receiving said paging frames transmitted by
5 said first base station to receiving said system parameters transmitted by said
6 second base station and back.

- 1 24. A mobile station, comprising:
2 a control head;
3 a transceiver unit, comprising
4 a transmitter;
5 a receiver; and
6 a logic control assembly at least partially controlled by said control
7 head; and
8 an antenna assembly connected to said transceiver unit;
9 wherein said logic control assembly controls the operation of said transceiver
10 unit to scan for and evaluate transmitted parameters of at least one base
11 station under evaluation without missing paging frames from a registered
12 base station.
- 1 25. The mobile station of Claim 24, wherein receipt of a first paging frame from said
2 registered base station triggers said transceiver unit to scan for and evaluate said
3 base station under evaluation.
- 1 26. The mobile station of Claim 24, wherein said transceiver unit further comprises
2 memory and said logic control assembly executes programs in said memory to
3 scan for and evaluate said transmitted parameters.
- 1 27. The mobile station of Claim 24, wherein said transceiver unit receives said
2 parameters only when said registered base station is not transmitting said paging
3 frames.
- 1 28. The mobile station of Claim 24, wherein said transceiver unit stops scanning for
2 said parameters once said parameters are received.
- 1 29. The mobile station of Claim 24, wherein said transceiver unit can receive said
2 parameters only during a predetermined amount of time said predetermined
3 amount of time being dependent on the architecture of said mobile station.
- 1 30. The system of Claim 24, wherein said transceiver unit can receive said
2 parameters only during a predetermined amount of time, said amount of time
3 being dependent on the amount of time between said paging frames for said
4 mobile station transmitted by said registered base station.

1 31. The system of Claim 24, wherein said transceiver unit can receive said
2 parameters only during a predetermined amount of time, said amount of time
3 being dependent on the amount of time required for said mobile phone to switch
4 from receiving said paging frames transmitted by said registered base station to
5 receiving said parameters transmitted by said base station under evaluation and
6 back.

TIME




Figure 1
(Prior Art)




Figure 2
(Prior Art)




Figure 3




Figure 4




Figure 5

600




Figure 6

INTERNATIONAL SEARCH REPORT

Inter. Application No

PCT/US 00/08470

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 260 988 A (D AVELLO ROBERT F ET AL) 9 November 1993 (1993-11-09) column 10, line 66 -column 11, line 34 ----	1,3-6,8, 9,11-14, 16-19, 21,22, 24-27, 29,30
X	WO 98 49852 A (ERICSSON TELEFON AB L M) 5 November 1998 (1998-11-05) page 11, line 7 - line 24 ----- -/--	1,3-6,8, 9,11-14, 16-19, 21,22, 24-27, 29,30

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

7 July 2000

Date of mailing of the international search report

14/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pecci, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/08470

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>US 5 613 208 A (BLACKMAN HANS ET AL) 18 March 1997 (1997-03-18)</p> <p>column 3, line 25 - line 40 column 5, line 44 -column 7, line 32 claim 1</p> <p>-----</p>	<p>1,3-5,8, 9,11-13, 16-18, 22,24, 26,27,30</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/08470

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5260988 A	09-11-1993	BR 9205852 A	28-06-1994
		CA 2106063 A,C	07-08-1993
		CN 1076320 A,B	15-09-1993
		FR 2687872 A	27-08-1993
		GB 2271039 A,B	30-03-1994
		IT 1261760 B	03-06-1996
		JP 2864734 B	08-03-1999
		JP 6506817 T	28-07-1994
		KR 9711532 B	11-07-1997
		MX 9300640 A	01-09-1993
		WO 9316548 A	19-08-1993
		US 5842122 A	24-11-1998
WO 9849852 A	05-11-1998	AU 7355198 A	24-11-1998
		EP 0979581 A	16-02-2000
		SE 9701617 A	30-10-1998
US 5613208 A	18-03-1997	AU 2659195 A	04-01-1996
		DK 134396 A	25-11-1996
		FI 964882 A	05-12-1996
		NO 965197 A	31-01-1997
		SE 9604326 A	29-01-1997
		WO 9534178 A	14-12-1995

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)